

It's what your business is all about – working hard and carrying more. It's why you need a heavy-duty chassis that will do the same – because yours is a roll up your sleeves and get it done type of business. Whether it's laundry, linen, tool, plumbing, delivery or utility, you need a strong platform that you can rely on.

At Workhorse we have that same roll up your sleeves attitude. A relentless determination to create solutions that not only meet your needs, but also give you more choices.

## Need a heavy-duty platform?

Workhorse has the industry proven W62, and it's tough as nails. Durable and dependable, with the kind of practical innovations that improve efficiency, reduce your maintenance costs and strengthen your bottom line. And with Meritor<sup>®</sup> Quadraulic<sup>™</sup> brakes and Stabilride<sup>™</sup> and Vari-Rate suspensions, the W62 has the performance, maneuverability and toughness you need in the 17,000 – 23,500 lb. GVWR range.

## Considering gas as well as diesel?

Only the W62 offers both. The MaxxForce® 7 diesel is a robust, incredibly quiet and fuel efficient engine with longer maintenance intervals to keep your costs down. The legendary GM Vortec® 6.0L gas engine is a fuel efficient and cost effective engine that can serve as an alternative to diesel.



## Don't want the complicated mess of SCR?

The W62 can help. To avoid the added pounds, extra equipment and lost payload due to the competitor's SCR diesel, choose a Workhorse and experience a completely different approach to 2010 emissions.

At Workhorse, we're determined to deliver what you need, not what we sell. See your Workhorse dealer today and make a W62 your next heavy-payload walk-in truck platform.

WORKHORSE® W62	MY 2011 GAS				MY	MY 2010 DIESEL		
	17,000	19,500	23,000	23,500	17,000	19,500	23,500	
	GM Vortec® 6.0L V8 299 HP @ 4,400 rpm 357 lbft. torque @ 4,400 rpm			MaxxForce®7, 6.4L V8 230 hp @ 2,600 rpm 560 lbft. torque @ 1,400 rpm				
RANSMISSION								
Allison 1000HS with park pawl	S	S	NA	NA	S	S	NA	
Allison 2000HS with park pawl	NA	NA	S	S	NA	NA	S	
ransmission ratios (1) 3.10 (2) 1.81 (3) 1.41 (4) 1.00 (5) 0.71 (R) 4.49								
RONT AXLE			_			_	•	
Vestport 8,000 lbs. capacity	S	S	S	S	S	S	S	
RONT SUSPENSION						0		
Ctabilride™ 6,500 lbs.		0				S		
Stabilride™ 7,000 lbs.	S	S			S			
Ctabilride™ 7,500 lbs.			S	S		0	S	
Stabilride™ 8,000 lbs.			3	3			3	
REAR AXLE						0		
Dana S110 13,000 lbs.					S	S		
Dana S110 13,500 lbs.	S	S						
Dana S130 15,500 lbs.			S	S			S	
.30:1 rear axle ratio					S			
.88:1 rear axle ratio	S	S						
.13:1 rear axle ratio			S	0		S	S	
.86:1 rear axle ratio				S				
EAR SUSPENSION DIESEL								
/ari-Rate 12,000 lbs.	S				S			
/ari-Rate 13,000 lbs.		S				S		
/ari-Rate 15,000 lbs.			S					
/ari-Rate 15,500 lbs.				S			S	
VHEELBASE SELECTIONS								
57 in.	S	S	S	S	S	S	S	
78, 190, 208, 218 in.	0	0	0	0	0	0	0	
BRAKES								
Meritor® Quadraulic™ calipers-64mm	NA	NA	NA	NA		S		
Meritor Quadraulic calipers-70mm	S	S	S	S			S	
Meritor WABCO 4-channel ABS system with full J 1939 diagnostic capability	S	S	S	S	S	S	S	
TEERING								
F Servocom® 8095 variable ratio power steering	S	S	S	S	S	S	S	
VHEELS								
25/70R19.5 (gray standard) (black or white optional)	S	S	NA	NA	S			
45/75R19.5	0	0	S	NA		S	S	
45/75R22.5 (Gray)	NA	NA	NA	S		S	S	
45/75R22.5 (Aluminum)	NA	NA	NA	0	NA	NA	NA	
lug and lug covers (optional with aluminim wheels only)	NA	NA	NA	0	NA	NA	NA	
RAME								
Constant section, full-depth frame. Maximum section 9.63 x 3.9 x .25 in; section modulus 10.13: resistance to bending movement 506,500 lbs.	S	S	S	S	S	S	S	
STANDARD FEATURES								
nstrument cluster with info center, tilt steering column,	S	S	S	S	S	S	S	
brake/transmission shift interlock, daytime running lights provision								
IMITED WARRANTY								
years or 50,000 miles* on chassis transferable, not including body	S	S	S	S	S	S	S	
years or 150,000 miles* on diesel engine	S	S	S	S	S	S	S	
years or 50,000 miles* on gas engine	S	S	S	S	S	S	S	
years or 50,000 miles on gas engine years and unlimited mileage on Allison transmission	S	S	S	S	S	S	S	
ROADSIDE ASSISTANCE (all models)	0	3		<u> </u>				
4 hour, seven days a week; 3 years or 36,000* transferable	S	S	S	S	S	S	S	

S=Standard 0=Option



A NAVISTAR COMPANY

922 South State Route 32 Union City, IN 47390 www.workhorse.com 877-BY HORSE (877-294-6773)

♣ As part of Workhorse's ongoing commitment to the environment, this document is designed to be electronic. If you choose to print it please do your part and use recycled paper and EcoSmart™ inks.

Workhorse, the Workhorse logo and MaxxForce are trademarks of Navistar, Inc. All illustrations and specifications in this publication are based on the latest information available at the time of content approval. Product photos that appear in this publication may depict alternate product configurations and/or options. All marks are trademarks of their respective owners. ©2010 Workhorse Custom Chassis All rights reserved. WCCC-670 0910 Litho in USA Part No. WSL091310